



## Multipurpose Permanent Glue (I254)

This spray is amazing! It dries immediately and can be used on different materials. It is resistant to high temperature. These are its secrets, you just have to try it!



**HOW TO USE:** Shake Well before use. Clean the part to glue. Spray the product on one of the surfaces to glue. Overlap the other one sticking on the glued part applying strong pressure. The initial taking is rapid but the complete adhesion happens within 24 hours.

Quantity	400 ml
Barcode	EAN 13: 8034108890296
Box / Case	12 pz

**MULTIPURPOSE PERMANENT GLUE** – Particularly useful for gluing rubber, metal, vinyl, fabric, wood, and plastic materials. High heat resistance even with prolonged exposure. Also, highly resistant to plastic agents in general. It comes with an adjustable spray nozzle.

### Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Colorless
Odour	Characteristic of solvent
Relative density	at 20°C 0,66 ÷ 0,70 g/ml
Flash point	Und.0° C extremely flammable
Pressure at 20°C	4/6 bar
Dry residue	38 - 40 %
Viscosity at 20°C	240 - 300 mPa·s. (Visc. Brookfield RVT)
Tack (ropiness)	Very strong
Taking	rapid
Drying times	Min. 3' – Max 6'
Adhesive type	Rubber thermoplastic adhesive in solvent
Range temperature	÷ 80°C (peak)

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 35°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**